







ZINFLASH



-  Can be fixed with Hall Clips and pointed with sealant or mortar.
-  Can be dressed over tile profiles.
-  Thin enough to be used as a soaker.
-  Environmentally-friendly as it is 100% recyclable.
-  Light weight and easy to handle.
-  No need for costly lap and gap sealant or watertight tape.

ZinFlash[®] is a soft zinc that is exceptionally malleable and ideally suited for flashings. It is flexible, pliable, and simple to dress to the contours of a roof and the profile of a tile.

ZinFlash[®] can be used in all applications traditionally associated with lead; canopies, dormers, bay windows, gutters etc. finally weathering to a light grey colour.

ZinFlash[®] conforms to BSEN: 1179 - 2003.

ZINFLASH

Advice on use

ZinFlash® can be easily cut with snips and formed with the usual plumber's tools, by hand or by machine. It can be welded and is easy to solder with Tinman's solder.

ZinFlash® poses no risk of run-off staining and therefore does not require an application of patination oil.

ZinFlash® can be used in a range of applications, some of which are listed below:

Apron flashings	Slate soakers	Dormers
Chimney flashings	Rooflight flashings	Flue flashings
Abutment flashings	Gutters	Saddle flashings
Soil vent pipe flashings	Sills, door-windows	Valleys
Edge Weatherings	Continuous step and cover flashings	
Bay, canopy and dormers	Parapet and cornice copings	

ZinFlash® can also be used on ecclesiastical and aged building renovations and repairs.

Lot sizes

150mm x 12m x 0.60mm
250mm x 12m x 0.60mm
300mm x 12m x 0.60mm
380mm x 12m x 0.60mm
450mm x 12m x 0.60mm

Health & Safety Advice



Handling: The usual precautionary measures should be adhered to when handling metal products.



No additional precautions required in its solid state.



Remove metal residues from skin after working with metal by washing with Premium Metwash - Soap and Bodywash.

Storage

Store under dry conditions, protect from humidity and keep away from water. Do not store with acids or alkalis (caustic solutions).

Product Description and Properties

Thickness	0.60mm
Weight / m2	ca 4.44 kg
Length of roll	ca 12 m
Colour	Silver grey
Melting point	420°C

Weathering

Rural	50-100 years
Urban	Over 50 years
Marine	Over 40 years
Heavy Industrial	Over 25 years

This data is based on our present knowledge; it will not constitute a guarantee for any specific product feature and will not establish a legally valid contractual relationship